

PRODUCT INFORMATION



- Convenient cleaning of the oven thanks to the ashtray located under the grille.
- Easy firing guaranteed by cast iron grate with independent aeration.
- Outstanding durability of the furnace is achieved thanks to the construction that uses multifaceted bending of steel from the large pieces.
- The small size of the furnace and the low value of heating power range makes the furnace ideal for smaller rooms.
- Possibility to connect flue pipe from the top or back with massive cast iron flue.
- Possibility to use the top heating plate when flue pipe is connected on the back.
- The furnace is made of high-quality boiler steel P265GH type.
- The furnace has an air steering profile to keep the glass from heat-resistant ceramic glass used in all Hitze fireplaces (up to 800 ° C).
- The use of two deflectors (ceramic and steel) provides ecological combustion.

Nominal power [kW]	6,5
Heating load range [kW]	3-8,5
Thermal efficiency [%]	84 %
CO emission (at 13% O ₂) [g/m ³]	0,948
Dust emission [g/m ³]	0,026
Average fuel consumption [kg/h]	1,86
Glass dimensions [mm]	381x530x381
Flue diameter [mm]	150
Inlet diameter [mm]	123
Masa wkładu [kg]	179
Efficiency factor	111,8
Energy efficiency class	A+

